


















































Model:	Digital Video Record		INC GST
3290S	New: YAHA 3290S Stand alone 4 Channel Real time DVR, H264 Baseline, USB, Backup, Remote control, Remote Access, 5 network Client Support		\$ 375.70
3290V	New: YAHA 3290SV Stand alone 4 Channel Real time DVR, H264 Baseline, USB, Backup, Remote control, Remote Access, 5 network Client Support, with VGA, Direct connect to LCD Monitor		\$ 427.70
3299M	New Stand alone 9 Channel DVR Model: Yaha3299M Remote, Backup: USB . DVDRW, HDD , Network, VGA Port . Can direct connect to LCD Monitor		\$ 737.50
3296M	New Stand alone 16 Channel DVR Model: Yaha3296 Remote, Backup: USB . DVDRW, HDD , Network, Can direct connect to LCD Monitor		\$ 987.50
114M	DVR Card:114M 4-Channel 50F, DVR Card. MPEG4 software compression, Display solution 765 x 576		\$ 97.50
818M	Yaha Digital Video Recorder Card DVR-818M PCI 8 Channels Real time, H.264 optimized, Yaha Digital Video Recorder Card DVR-818M PCI 8 Channels Real time, H.264 optimized high recording definition, especially when there is intense movement, Display resolution: 640 X 480, 352 X 288, 320 X 240		\$ 312.00
1408	DVR Card: Digital Video Recorder Card 1408 8 Channel Real Time PCIE, 11-bit ADCs bring better image quality ,Image Resolution: 704 X 576, 352 X 288 Video total frame rate :240 fps in NTSC, 200 fps in PAL		\$ 325.00
605N	DVR Card , PCI , 16 channel video, 4 channel audio, 1 channel TV out, Total 120FPS, MPEG-4, One PC support 1 card, Can be integrated with POS systems , Windows XP/2000		\$ 253.50
616N	DVR Card , PCI , 16 channel video, 8 channel audio, 1 channel TV out, Total 240 FPS, MPEG-4, One PC support 1 card, Can be integrated with POS systems , Windows XP/2000		\$ 377.00
1416	DVR Card: Yaha Digital Video Recorder Card 1416, 16 channel real time monitoring , PCIE 11-bit ADCs bring better image quality ,Image Resolution: 704 X 576, 352 X 288 , Video total frame rate : 480 fps in NTSC,400 fps in PAL		\$ 475.00
	Dome Camera		
D4212-3.6	YAHA-D4212 Dome,1/4" Sharp 420TV Lines,PAL:500(H)x582(V) NTSC: 510(H)x492(V) 0.8Lux/F1.2,Lens: 3.6mm		\$ 63.70
D4212-2.8	YAHA-D4212 Dome,1/4" Sharp 420TV Lines,PAL:500(H)x582(V) NTSC: 510(H)x492(V) 0.8Lux/F1.2,Lens: 2.8mm		\$ 63.70
D4212IR-3.6	Yaha 4212IR Dome,1/4" Sharp Len:3.6mm,420TVL Infra Red , PAL:500(H)x582(V), Auto Gain Control: On/Off Selectable,Back Light Copensation:n/Off Selectable,S/N Ratio:□24pcs, Infrared Lamps Distance: 20M, Minimum illumination: 0 Lux, Video Output:□1 Vpp,75 Ohms		\$ 84.50
D4212IR-6	Dome, 1/4" Sharp Len 6mm,420TVL Infrared Dome Camera, PAL:500(H)x582(V), Auto Gain Control: On/Off Selectable,Back Light Copensation:n/Off Selectable,S/N Ratio:□24pcs, Infrared Lamps Distance: 20M, Minimum illumination: 0 Lux, Video Output:□1 Vpp,75 Ohms		\$ 84.50
3412DU	YAHA-3412DU Dome 1/3" Sony Super HAD CCD, 420 TVL , 3.6mm Lens		\$ 110.50
3412DK	YAHA-3412DK Dome 1/3" Sony Super HAD CCD, 420 TVL , 3.6mm Lens		\$ 110.50

D414V4	Yaha D414V4 1/3" Sony CCD Image Sensor; 420TVL Vandal proof Dome Camera, PAL:500(H)x582(V), Auto Gain Control: On/Off Selectable,Back Light Copensation:n/Off Selectable,S/N Ratio:□24pcs, Infrared Lamps Distance: 20M, Minimum illumination: 0 Lux, Video Output:□1 Vpp,75 Ohms, 3.6/6mm Lens Optional.		\$ 136.50
6210CT	1/3" Sony super HAD Image Sensor; 420TVL, 0.5Lux / F1.2, Vandal-proof Dome; 18 pcs IR LEDs; High Resolution; High Sensitivity		\$ 136.50
M62L/T	Yaha M62L/T Varifocal Dome camera with Day&Night, Color Sony 1/3" 420(color) /600tvl(B/W) Varifocal Lens 4-9mm,Manual Iris		\$ 143.00
D652IRV3	Yaha D652IRV3 550TV Line, 0.05lux, 1/3"Sony CCD, Vandal Proof Dome , Water proof / ip66 Len 3.6 mm, 24 VCS IR Led Ir distance: 20m		\$ 227.50
PTZ24XS	PTZ Dome Color 1/3" SONY, 420TV Lines ,360 Degree Pan Tilt IR Dome camera,Pan range: 0°~360° Continue (Not 355°)Tilt range: 0°~90° Flip,Pan Speed: Max 50%/sec,Preset: 16,RS485 control IR LED: 24pcs, IR working distance:20M,5-15mm dynamic varifocal lens (standard) 5-15mm dynamic varifocal lens, ize: Ø131x96mm; Weight: 1250g		\$ 377.00
PTZ24XSH	PTZ Dome Color 1/3" SONY, 480TV Lines ,360 Degree Pan Tilt IR Dome camera,Pan range: 0°~360° Continue (Not 355°)Tilt range: 0°~90° Flip,Pan Speed: Max 50%/sec,Preset: 16,RS485 control IR LED: 24pcs, IR working distance:20M,5-15mm dynamic varifocal lens (standard) 5-15mm dynamic varifocal lens, ize: Ø131x96mm; Weight: 1250g		\$ 400.00
PTZ24XSHC	PTZ Dome Color 1/3" SONY, 540TV Lines ,360 Degree Pan Tilt IR Dome camera,Pan range: 0°~360° Continue (Not 355°)Tilt range: 0°~90° Flip,Pan Speed: Max 50%/sec,Preset: 16,RS485 control IR LED: 24pcs, IR working distance:20M,5-15mm dynamic varifocal lens (standard) 5-15mm dynamic varifocal lens, ize: Ø131x96mm; Weight: 1250g		\$ 437.50
PTZSDK24	Remote Control Special design for PTZ24,PT Dome controller, IR remote controler: Support 99pcs cameras RS-485 communication, Baud rate: 2400,4800 and 9600Bps Communication distance: Max.1200m, Weight: 350g		\$ 104.00
PTZ 78ID	PTZ Dome,78ID,: 1/4' Sony 480TVL, B/W0.001Lux, 0.2LUX(color)/0.02LUX(B/W) ,Lens: F=1.6,F=3.9mm~85.8mm , 22x optical zoom, 10x digital zoom.355° panning,Pan speed: 0-15 Degree,Baud rate: 2400/4800/9600		\$ 1,144.00
SD-858	PTZ Dome,SD-858,: 1/4' Sony 480TVL ,Illumination: 0.2LUX(color)/0.02LUX(B/W) Auto:Iris, Focus. Pan speed: 25 Degree,Tilt speed: 25 Degree, Baud rate: 2400/4800/9600		\$ 1,105.00
Full Body Camera:			
P4240	YAHA P4240 Surveillance Camera 1/4"Sharp, 420 TV Lines.PAL:752(H)x582(V) , Auto Iris Lens: Video/DC. Min. illumination: 0.8Lux/F1.2, 0.3Lux/F1.2. Auto Elec. Shutter: 1/50 (1/60) - 1/100,000secVideo Output: 1.0Vp-p75 ohms		\$ 91.00
P3240	YAHA-P3240 1/3"SHARP, 420 TV Lines.PAL:512(H)x582(V) , NTSC: 510(H)x492(V),Signal System: PAL/NTSC,Auto Iris Lens: Video/DC, Gain Control: On/Off, White Balance: Auto/Manual, Backing Light Compensation: On/Off, Min. illumination: 0.8Lux/F1.2, 0.3Lux/F1.2, S/N Ratio: >48db, Gamma Characteristic: 0.45, Auto Elec. Shutter: 1/50 (1/60) - 1/100,000sec, Video Output: 1.0Vp-p75 ohms		\$ 97.50

P450C	1/3" Sony CCD 420TVL, 0.01lux, Day/Night Camera		\$ 123.50
P3496	Yaha P3496 1/3" Sony 420TVL, Color and B/W Mode Switch Automaticly; High Sensitivity		\$ 123.50
610CP	Spy Camera: 610CP , Miniature Size ; Pinhole Lens Selectable ; High Sensitivity; High Resolution		\$ 123.50
811B1	YAHA-811B1 Bullet Camera, 1/3" Sony Super HAD CCD. 420TVL, 3.7 mm pinhole Lens,0.5Lux@F1.2,S/N Ratio:More than 48dB.Auto Tracking White Balance,		\$ 123.50
811B2	YAHA-811B2 Bullet Camera, 1/3" Sony Super HAD CCD. 420TVL, 3.6 mm Board Lens,0.5Lux@F1.2,S/N Ratio:More than 48dB.Auto Tracking White Balance,		\$ 123.50
W6204A	YAHA-W6204A IR Medium Distance IR Weather proof Camera. 4mm Lens , 1/3" Sony CCD, 420TVL.PAL:752x582 NTSC:768x494, Auto Gain Control: On/Off Selectable,Back Light Copensation:n/Off Selectable,S/N Ratio :□24pcs,Infrared Lamps Distance: 20M, Minimum illumination: 0 Lux, Video Output:□1 Vpp,75 Ohms		\$ 128.70
W6204B	YAHA-6204B IR Medium Distance IR Weather proof Camera. 8mm Lens , 1/3" Sony CCD, 420TVL.PAL:752x582 NTSC:768x494, Auto Gain Control: On/Off Selectable,Back Light Copensation:n/Off Selectable,S/N Ratio :□24pcs,Infrared Lamps Distance: 20M, Minimum illumination: 0 Lux, Video Output:□1 Vpp,75 Ohms		\$ 128.70
W6204C	YAHA-6204C IR Medium Distance IR Weather proof Camera. 12mm Lens , 1/3" Sony CCD, 420TVL.PAL:752x582 NTSC:768x494, Auto Gain Control: On/Off Selectable,Back Light Copensation:n/Off Selectable,S/N Ratio :□24pcs,Infrared Lamps Distance: 20M, Minimum illumination: 0 Lux, Video Output:□1 Vpp,75 Ohms		\$ 128.70
816L	Yaha816L:□24pcs,Infrared Lamps Distance: 20M, Minimum illumination: 0 Lux, Video Output:□1 Vpp,75 Ohms		\$ 156.00
650C	YAHA 650C 550TVL ,0.05Lux. 1/3'Sony super had CCD. Signal System: PAL/NTSC,Auto Iris Lens: Video/DC, Gain Control: On/Off, White Balance: Auto/Manual, Backing Light Compensation: On/Off, S/N Ratio: >48db, Gamma Characteristic: 0.45, Auto Elec. Shutter: 1/50 (1/60) - 1/100,000sec, Video Output: 1.0Vp-p75 ohms		\$ 240.50
216C	Yaha 216C Outdoor Image Device:1/3 OmniVision CMOS, Validity pixel:PAL:628X582,NTSC:510X492,Horizontal Definition:320Line, Scan Frequency:PAL/NTSC: 50Hz/60Hz, Minimum Illumination:3Lux/F1.2, Power Supply: DC 8V/200mA. Size:115x38x40mm,		\$ 63.70
808C	Yaha 808C CCD Camera apparatus :1/4" picture senser, System: PAL or NTSC, Picture area : PAL:5.78 x 4.19 mm		\$ 84.50
901C	Yaha 901C CCD Image Device:1/3" Sharp CCD, Valid pixel:PAL:512x582, Function: BLC		\$ 97.50

P470	YAHA CCD P470A Surveillance ,1/4"Sharp, 470 TV Lines.PAL:752(H)x582(V) , NTSC: 768(H)x494(V) . Signal System: PAL/NTSC. Auto Iris Lens: Video/DC. Gain Control: On/Off. White Balance: Auto/Manual. Backing Light Compensation: On/Off. Min. illumination: 0.8Lux/F1.2, 0.3Lux/F1.2. S/N Ratio: >48db. Gamma Characteristic: 0.45. Auto Elec. Shutter: 1/50 (1/60) - 1/100,000sec. Video Output: 1.0Vp-p75 ohms		\$ 104.00
CQ48A242N	YAHA CQ48A242N Digital zoom in zoom out , 1/4-inch Super HAK Color 470 TV Lines CCD, Minimum Illumination: 1.0Lux/0.02Lux;Zoom: Optical times: 22, digital times: 11		\$ 455.00
NEW: W6211	YAHA-W6211 IR Medium Distance IR Water proof Camera. 1/3"Sony EX-View, COLOR CCD, 420TVL, PAL:512(H)x582(v), 1.0 LUX (0LUX When IR LED turns on), Auto Tracking White Balance,PAL/NTSC Available, 12pcs IR LEDs, Strong IR light, Wide Angle,Longest IR Distance 60m, Built-in 25mm lens, DC12V. Nitrogen gas inside the camera reduces fogging phenomenon. Operating Temperature -10C ~ +50C,		\$ 370.50
IP Camera			
AVI-201Z/F36	AVTECH AVI-201Z/F36 1/3.6" Color IP Camera (cost-effective), LAN Speed 10/100 Based-T Ethernet, Frame Rate NTSC:30, PAL:25, Number of Online Users 10, Security Multiple user access levels with password, Web management software, Video Compression, MPEG4 / MJPEG, Image Sensor 1/3.6" image sensor, Lens f3.6mm / f4.6mm,Viewing Angle 80° / 55.6°, Shutter Speed 1 / 60 (1/50) to 1 / 100,000 sec,Power 12VDC, 0.2A.		\$ 143.00
ZN-YH305	GANZ ZN-YH305 CS Mount IP Camera, 1/4 inch Colour CMOS sensor, Real-time MPEG-4 compression, Power over Ethernet (PoE) built-in, Digital I/O for external sensor and alarm, Built-in omni-directional microphone, Resolution: 640(H) x 480(V), Electronic Shutter: 1/60~1/15,000 second, Includes 4mm, F2.0 lens		\$ 437.50
ACM-3401	ACTi 1.3 Megapixel IP Dome Security Camera ,1/3" Micron Progressive Scan CMOS,Integrated f4.2mm / F1.8 Megapixel lens,0.5 Lux at F1.0,Selectable MPEG-4 / MJPEG compression,Up to SXGA(1280x1024) resolution at 8 FPS, Multi-stream with variable frame rate in the same compression, Two-way audio supported, Hardware motion detection,DC 12 V or Power over Ethernet (IEEE 802.3af) supported, Surface and wall mount supported - 10° ~ 50° 133(Ø) x 99(H) mm		\$ 643.50
Wireless Camera			\$ -
	R301+ 208 Wireless Image Device:1/3OmniVision CMOS, Validity pixel:PAL:628X582,NTSC:510X492, Output frequency:2.4G. Receiver:Size:96X79X30mm, Open Transmiss		\$ 136.50
	Yaha R810 3.5" TFT LCD wireless monitor and receiver		\$ 257.40
	Yaha R810 3.5" TFT LCD wireless monitor and receiver + 812C Infrared Camera (1 + 1)		\$ 370.50
	Yaha R810 3.5" TFT LCD wireless monitor and receiver + 220 Infrared Camera (1 + 1)		\$ 357.50
	Yaha R310 Receiver and 802C Wireless Surveillance infrared camera		\$ 156.00
	Yaha R420 Receiver and 812C Wireless Surveillance infrared camera		\$ 182.00
Camera Outdoor Housing and Stands			

	Camera Outdoor Box Silver: Box size:34.5x10.7x11cm , Stand Size:29x9x7.5cm		\$ 39.00
	Camera Outdoor Box Beige: Box size: 32x12x11.5cm , Stand Size:29x9x7.5cm		\$ 39.00
	Camera Stand 01S Size: 135x58mm (High x Base)		\$ 6.50
	Camera Stand 02S Size: 155x88mm (High x Base)		\$ 6.50
	Camera Stand 04S Size: 265x90mm (High x Base)		\$ 10.40
	Camera Stand 06S Size: 165x65x85mm (LxWxH)		\$ 13.00
	Camera Cable		
	1 in 4 Camera power Cable		\$ 5.20
	1 in 8 Camera power Cable		\$ 10.40
	10 Meter Pre-made video & power Cable		\$ 11.70
	20 Meter Pre-made video & power Cable		\$ 20.80
	30 Meter Pre-made video & power Cable		\$ 31.20
	50 Meter Pre-made video & power Cable		\$ 52.00
	High quality RG59 coaxial cable 100 meter/roll		\$ 104.00
	High quality RG59 coaxial cable 200 meter/roll		\$ 149.50
	High quality RG59 coaxial cable with Figure 8 cable 100 meter/roll		\$ 188.50
	Figure-8 cable 100 meter/roll		\$ 39.00
	Camera Power Supply		
	12VDC 1 A		\$ 13.00
	12VDC 2 A		\$ 19.50
	12VDC 5 A		\$ 32.50
	Camera Connector		
LLT-202E	Video Balun - 1 Channel passive video transceiver. Receiving and transmitting video signals over UTP cable without using the power supply.		\$ 19.50
Balun213	Video Balun Passive Video Balun-BNC Male to RJ45 female(power)		\$ 39.00
	BNC male to RJ45 female with power cord, Video only		\$ 78.00
	AVerMedia TV2VGA, Allows to display video clips on TV and VGA monitor		\$ 1.30
	BNC-09 BNC-Male 3 pcs crimp connector, 0.9mm center pin		\$ 1.30
	BNC-T1 BNC male to 2 BNC female T connector		\$ 1.30
	BNC-F BNC female to female barrel connector		\$ 1.30

	BNCM-RF BNC male to RCA female connector		\$ 1.30
	BNCF-RM BNC female to RCA male connector		\$ 1.30
	DC-2.1ML 2.1mm DC male connector with 15 cm cable		\$ 1.30
	DC-2.1FL 2.1mm DC female connector with 15 cm cable		\$ 1.30
	T-BNC-0.7 RG 59U BNC crimp plug, With 0.7mm centre pin		\$ 1.30
	T-BNC-F, BNC female to female barrel adaptor		\$ 1.30
	T-RCAM-BF, RCA male to BNC female Adaptor		\$ 1.30
	RG59-TS Rotary RG58/59 coaxial striper		\$ 19.50
	RG59-TC Heavy duty ratchet Crimping tool		\$ 32.50
CAMERA LENS			
	Camera Lens C/CS Fix Iris Lens 2.8 mm 1/3": 130, 1/4": 98 degree		\$ 20.80
	Camera Lens C/CS Fix Iris Lens 4 mm 1/3": 80, 1/4": 64 degree		\$ 14.30
	Camera Lens C/CS Fix Iris Lens 6 mm 1/3": 53, 1/4": 38 degree		\$ 14.30
	Camera Lens C/CS Fix Iris Lens 8 mm 1/3": 40, 1/4": 30 degree		\$ 14.30
	Camera Lens C/CS Fix Iris Lens 12 mm 1/3": 28, 1/4": 19 degree		\$ 14.30
	Camera Lens C/CS Fix Iris Lens 16 mm 1/3": 19, 1/4": 15 degree		\$ 20.80
	Camera Lens 3.5-8 mm Auto Iris Lens		\$ 39.00
	Camera Lens 6-15mm Auto Iris Lens		\$ 52.00
	Camera Lens 6-60mm Auto Iris Lens		\$ 71.50
	Auto Iris Vari-Focal Lens 3.5 - 8 mm 1/3": 106.6-25.8 1/4":75.8-19.34		\$ 58.50